

STABILIZATION OF LINEAR CONTROLLABLE SYSTEMS BY MEANS OF BOUNDED CONTINUOUS NONLINEAR FEEDBACK CONTROL

Rodolfo Suárez, Julio Solís-Daun and Jesús Álvarez

*División de Ciencias Básicas e Ingeniería,
Universidad Autónoma Metropolitana-Iztapalapa, Apdo. Postal 55-534
09340, México, D.F., México.
Phone (5) 7244654 Fax (5) 7244653*

keywords: bounded control, stabilizing feedback control, controllable set, ellipsoidal estimates, finite-time Lyapunov function.

Abstract:

Stabilization of linear systems with bounded continuous stabilizing feedback control is a problem which has received little attention, due to the difficulty of being a nonlinear problem. It is known that any open-loop unstable linear system cannot be globally stabilized by bounded continuous control, and that saturation induces periodic solutions even in the open-loop stable case (see [7]).

The bounded continuous feedback stabilization (BCFS) problem has been addressed by two approaches. One approach is the saturated linear feedback (SLF) : design a globally stabilizing linear feedback and then consider its saturation. The resulting feedback is continuous and piecewise linear. In [7] the problem of determining the set of initial conditions which can be driven to the origin, i.e., the stability region (SR), by means of a SLF control, is considered. The other approach is the bounded continuous nonlinear feedback (BCNF) : design a nonlinear bounded continuous control, which possible does not reach its limits, to solve the problem. In this direction, it has been proved in [6] that any system which eigenvalues have nonpositive real part, can be globally stabilized by a BCNF control. A technique to construct the feedback control has been proposed recently in [9] extending the "nested saturations" approach developed by [8] (specialized to the n -th order integrator).

There are examples of systems (specifically the n -th order integrator [2]) which can be globally stabilized by the BCNF approach but not by the SLF one. The use of a nonlinear feedback control design is suggested by the following argument : as gains of a system with a SLF control are decreased, the system SR is enlarged. So then, it is natural to propose that gains should be designed so that they are small when the system is far from the

origin, and increase when the system approaches the origin. The type of variable-gain control functions which we consider are of the form : $u(x) = k^T(x) x$ (where $(\cdot)^T$ denotes transpose).

The design method of a BCNF control proposed in this paper, is based in the approximation technique of controllable sets developed in [1,4]. The controllable sets are internally approximated by means of ellipsoids. The design idea is to define the control function in such a way that the closed-loop vector field points in the direction normal to the ellipsoids. The resulting feedback is bounded, continuous and drives the initial points to the origin in finite time [4]. A redesign of the finite-time stabilizing feedback in a neighborhood of the origin, yields a BCNF control which solves the BCFS problem. This procedure allows us to address the stabilization problem of open-loop unstable systems. The technique is applied to the two-dimensional case and to the n -th order integrator, for which the BCNF control function is globally defined and can be explicitly obtained. An application of this technique to a continuous stirred tank reactor has been presented in [5].

References

- [1] F.L. Chernous'ko, Ellipsoidal estimates of a controlled system's attainability domain, *J. Applied Maths. Mech.*, 45 (1982), 7-12.
- [2] A.T. Fuller, In-the-large stability of relay and saturating control systems with linear controllers, *Int. J. Control*, 10 (1969) 457-480.
- [3] V.A. Komarov, Estimates of reachable sets for linear systems, *Math. USSR Izvestiya* 25, No.1 (1985) 193-206.
- [4] V.A. Komarov, Design of constrained controls for nonautonomous linear systems, *Automatic and Remote Control*, 10 (1985) 1280-1286.
- [5] J. Solis-Daun, J. Alvarez and R. Suárez, Bounded finite time stabilization for planar feedback linearizable systems: application to a continuous stirred tank reactor, *Proceedings of the American Control Conference*, Chicago, Il., (June 1992) 1018-1022.
- [6] E.D. Sontag and H.J. Sussmann, Nonlinear output feedback design for linear systems with saturating controls, *Proceedings of the 29th Conference on Decision and Control*, Honolulu, Hawai (Dec. 1990) 3414-3416.
- [7] R. Suárez, J. Alvarez and J. Alvarez, Linear systems with single saturated input: stability analysis. *Proceedings of the 30th IEEE Conference on Decision and Control*, Brighton, England (Dec. 1991) 223-228.
- [8] A.R. Teel, Global stabilization and restricted tracking for multiple integrators with bounded controls, *Systems and Control Letters* 18 (1992) 165-171.
- [9] Y. Yang, H.J. Sussmann and E.D. Sontag, Global stabilization of linear systems with bounded feedback, *Preprints of IFAC Conference on Nonlinear Control*, (June 1992).