

APPLICATION OF H_∞ METHODS TO THE CONTROL OF FLEXIBLE STRUCTURES

P. Coustal*

F. Delebecque†


R. Nikoukhah†

1 Introduction

In this paper we consider an H_∞ controller design methodology for flexible systems. We illustrate our approach with a complete treatment of a SISO example drawn from an industrial application. The proposed method avoids undesirable (lightly damped) pole-zero cancellations and yields a controller of the same order as that of the plant, using an alternative formulation to the mixed-sensitivity formulation of the standard problem. This new formulation poses particular difficulties in that its construction and its solution require manipulation of improper rational transfer matrices in state-space form.

2 Problem presentation

We consider the problem of controlling an optomechanical device used in a line of sight stabilization system [1, 2, 3]. The frequency response of the nominal plant is measured and identified using a least square method. The following figure shows the gain plot of the nominal plant.



3 Problem solution


3.1 H_∞ formulation

Robustness constraints on the control of flexible system are taken into account by a specific augmented plant which avoids lightly damped pole cancellations. Moreover, the synthesis ensures stability margin and high frequency robustness against spill-over effects by an adequate choice of the function penalizing the complementary sensitivity function.

Preventing pole-zero cancellation: In order to prevent lightly damped mode cancellations we penalize the function $G(I + GK)^{-1}$. In addition, G is decomposed into its partial fraction expansion $G = (\sum G_i)$. Some of the G_i 's represent lightly damped modes, and it is possible to introduce the functions $G_i(I + GK)^{-1}$ in the H_∞ criterion. This formulation allows to act independently on each mode, by penalizing the corresponding $G_i(I + GK)^{-1}$ function with a constant weighting function. (thus without increasing the order).

Stability robustness: It is obtained by penalizing the complementary sensitivity function $GK(I + GK)^{-1}$ with $W_3(s)$. Choosing $W_3(s)$ as constant in the low frequency domain is equivalent to set the quality factor Q of the closed loop system by ensuring the controlled open loop to be outside the corresponding M-circle. Choosing W_3 with a derivative action in the high frequency domain ensures robustness against spill-over effects. Finally, $W_3(s)$ is chosen as $Q^{-1}(\sum a_i s^i)$.

The diagram below represents the corresponding augmented plant.



*SFIM industries EA, 2 rue Kappler 92600 Asnières, France

†INRIA, Rocquencourt BP 105, 78153 Le Chesnay Cedex, France

In our application G_0 contains the rigid body mode of the system ($1/s^2$ factor) while G_1 and G_2 represent respectively the first two flexible modes of the model. The H_∞ problem is the following:

Find internally stabilizing K such that:


$$\left\| \begin{bmatrix} W_3 G K (I + G K)^{-1} \\ W_{50} G_0 (I + G K)^{-1} \\ W_{51} G_1 (I + G K)^{-1} \\ W_{52} G_2 (I + G K)^{-1} \end{bmatrix} \right\|_\infty < 1$$

3.2 Numerical solution

To constrain the controller to contain an integration term, the synthesis model is multiplied by $1/s$ i.e the synthesis is performed with the pre-integrated system. This leads to a G_0 plant containing a factor $1/s^3$. The augmented plant is then:

$$\begin{bmatrix} 0 & -W_3 \\ W_{50} G_0 & -W_{50} G_0 \\ W_{51} G_1 & -W_{51} G_1 \\ W_{52} G_2 & -W_{52} G_2 \\ G_0 + G_1 + G_2 & -G_0 - G_1 - G_2 \end{bmatrix}$$


With this formulation several difficulties arise which do not appear in the usual mixed sensitivity problem. G is strictly proper ($D_{21} = 0$), with imaginary-axis poles and W_3 non proper (polynomial). To overcome these difficulties, we introduce pre- and post-compensators to "normalize" the problem [4, 5].




In the previous figure, P does not satisfy the usual assumptions necessary to apply the Riccati based solution of the standard problem. However P_{tmp} does (with proper choice of M and N), and the final controller K is obtained from K_{tmp} by $K = N K_{tmp} M$.

The minimal realization of the augmented plant is obtained using the Ψ lab's primitives¹ which allow the manipulation of improper systems.

Below is the gain plot of W_3 :




The synthesis model (including the factor $1/s$) is the following:




The W_5 's weighting constants and the derivative action of $W_3(s)$ are chosen so that the H_∞ algorithm converges with $\gamma = 1$. The controlled open-loop is plotted in the Nyquist plane in order to analyze the stability of the system:

¹ Ψ lab is a scientific software package for control and signal processing developed at INRIA [6].



Clearly, the cancellations have been avoided, leading to a positive control of lightly damped modes. In addition, the open loop Nyquist plot is outside the specified M-circle ensuring the desired stability margin.

The following diagram shows the nominal plant, the function $G/(1+KG)$, the controller and the complementary sensitivity function $KG/(1+KG)$:



References

- [1] Coville, A., Abou-Kandil, H. and Coustal, P., (1991), Hyperstability and small gain: unified approach in the H_∞ frame, Proc. ECC.
- [2] Coustal, P. and Michelin, J. M., (1991), A discrete control for a two-axis sight system with structural flexibilities, Proc. ECC.
- [3] Michelin, J. M. and Coustal, P., (1991), Control of a sight system flexible structure: an H_∞ control design, Proc. CDC.
- [4] Nikoukhah, R. and Delebecque, F., On the design of H_∞ controllers when standard assumptions are not satisfied, submitted to ACC 93.
- [5] Copeland, B. R. and Safonov, M. G., (1992), Zero cancelling compensators for singular control problems and their application to the inner-outer factorization problem, Int. J. Robust and Nonlinear Control, 2.
- [6] Nikoukhah, R. and Delebecque, F., (1992), State-space representation of rational matrices in Ψ lab, INRIA report.