

A Parallel LU-Decomposition Algorithm for Modeling Discrete Signals by Polynomial or Exponential Interpolation

E. Angelidis and M. Kazantzakis

Keywords: Parallel Interpolation, parallel LU-Decomposition, Newton polynomials, FIR filters, processor arrays.

ABSTRACT. A parallel LU-decomposition algorithm for modeling polynomial or exponential signals using Newton interpolation is presented. The three solution stages required by the LU-decomposition procedure—(1) LU decomposition (2) forward substitution and (3) backward substitution—are performed in one stage with optimum speedup and efficiency. Constructing parallel graphs and task schedules we can obtain high performance in SIMD or MIMD computer architectures. The proposed algorithm is based on selecting properly triangular subsystems and deriving first-order linear recursive relations for the parallel evaluation of their elements we can also use array processors. Given n discrete sample points the modeling problem is solved in $2n$ computational levels if n processors are available. The obtained efficiency $E_n(n)$ and the speedup $S_n(n)$, for large n , take the ideal values of 1 and n , respectively. Increasing the number of computational levels we can restrict the number of processors in the range of 2 to $O(n)$. In the progressive case when a new $n+1$ sample appears, the proposed method requires only $4n$ time units to update the design parameters. The method can be extended to develop parallel algorithms for Fourier matrix factorization, DFT calculation, design of FIR digital filters, 2-D applications, etc.

I. INTRODUCTION

Interpolation methods have been used extensively in numerical mathematics, electrical engineering and digital signal processing [1], [2], [5]–[8]. The emergence of fast and efficient parallel algorithms particular in digital signal processing has meant that the general LU-method [9], [11], [15]–[17] and modifications [3], [12], [13] applied to polynomial or exponential signal modeling and FIR filter design have to be improved in order to obtain better efficiency and speedup with minimum computational requirements and economically number of processors. This can be achieved by selecting properly triangular subsystems in the LU-method and deriving simple recursive relations for their parallel computation. We implement this idea using lower triangular matrices with elements that can be obtained from the Newton interpolating polynomials and inverted upper triangular matrices with elements that can be calculated from simple recursive relation. Considering a time unit to be a floating point add, a floating point multiply, and some subscripting, the general parallel algorithm in [11] requires $T_p = n^2 - 1$ computational levels using $[n/2]$ processors with an efficiency of $E_p = 2/3$ for large n . The tridiagonal and bidiagonal factorization methods [3] use systolic arrays of n^2 processors to compute sequences of k -points DFT's. The Quadrant Interlocking Factorization methods [12], [13] need either a maximum number of $2(n-1)^2$ or $(n-1)^2$ processors working in parallel.

The serial algorithm described in [15], [18] needs $3n^2/2$ time units in $T_n=3n$ levels with an efficiency, $E_n(n)=0.5$ and a speedup, $S_n(n)=0.5n$.

The proposed algorithm provides the solution of the modeling problem in $2n^2$ time units in only $T_n=2n$ levels, with an efficiency, $E_n(n)=1$, and a speedup, $S_n(n)=n$, for large values of n . Thus the n processors are fully employed and allow to speed up the computation by a factor of n . Increasing the number of computational levels we can also restrict the number of the required processors in the range of 2 to n . Using the first-order linear recurrence relations derived for the solution of the forward and backward substitution subsystems we can also develop cyclic reduction parallel algorithms as described in [16], [17], suitable for processor arrays. In the progressive case when a new sample is added, we do not have to evaluate the unknown coefficients from the beginning, but only updating them with correction terms which depend on the last sample. In this case only $4n$ time units are required.

The proposed method can be extended to develop efficient parallel algorithms for Fourier matrix factorization, calculation of DFT, design of Finite Impulse Response (FIR) digital filters, 2-D applications etc.

REFERENCES

- [1] A. Zakhor and G. Alvstadt, "2-D Polynomial Interpolation for Nonuniform Samples", IEEE trans. on SP, Jan. 1992.
- [2] J.E.Cabezas and P.R.Diniz, "FIR Filters Using Interpolated Prefilters and Equalizers", IEEE Trans. Circuits Syst., Vol. 37, No. 1, Jan. 1990.
- [3] P.D. Gader, "Bidiagonal Factorization of Fourier Matrices and Systolic Algorithms for Computing Discrete Fourier Transform", IEEE Trans. on ASSP, Vol. 37, No. 8, Aug. 1989.
- [4] M. Berry and A. Sameh, "An Overview of Parallel Algorithms for the Singular Value and Symmetric Eigenvalue Problems", Journal of Comput. and Applied Mathematics 27 (1989) 191-213.
- [5] O.Egecioglu, E.Gallopoulos, K.Koc, "Parallel Hermite Interpolation: An algebraic approach", Computing 42, 291-307, (1989).
- [6] J. Diamessis, C. Therrien, "2-D Interpolation, Matrix Factorization and Applications to Signal Processing", ISCAS on Helsinki 1988.
- [7] T. Saramaki, Y. Neuvo, and S.K. Mitra, "Design of Computational Efficient Interpolated FIR Filters", IEEE Trans. Circuit Syst., Vol. 35, pp. 70-87, Jan. 1988.
- [8] J. Diamessis, C. Therrien, "Modeling Unequally Spaced 2-D Discrete Signals by Polynomials". Asilomar Conference on Signals, Systems and Computers, November 1986.
- [9] C. L. Nikias, A. P. Chrysalis, A.N. Venetsanopoulos, "The LU Decomposition Theorem and its Implications to the Realization of Two-Dimensional Digital Filters", IEEE Trans. on ASSP, Vol. 33, pp. 694-711, June 1985.
- [10] V. Zakharov, "Parallelism and Array Processing", IEEE Trans. on Computers, Vol. C-33, No. 1, Jan. 1984.
- [11] R. Lord, S. Kowalik, and S. Kumar, "Solving Linear Algebraic Equation on MIMD Computer" Association for Computing Machinery, Jun. 1983.
- [12] D.J. Evans and A. Hadjidimos "A modification of the Q.I.F. Parallel Method, Intern. J. Computer Math., Vol. 11, 1982.
- [13] D.J. Evans and M. Hatzopoulos, "A parallel Linear System Solver", Intern. J. Computer Math., Vol. 7, section B, 1979.

- [14] A. Sameh and K.Kuck, "On Stable Parallel Linear System Solvers", J. ACM 25, pp 81-91, Jan. 1978.
- [15] G.H. Golub and C.F. Van Loan, "Matrix Computations", 2nd Johns Hopkins University Press, 1989.
- [16] D. Bertsekas, J. Tsitsiklis, "Parallel and Distributed Computation, Numerical methods", Prentice Hall, Englewood Cliffs, N.J. 07632, 1989.
- [17] M. Quinn, "Designing Efficient Algorithms for Parallel Computers", McGraw-Hill, International Editions, 1989.
- [18] S.D. Conte and C. de Boor, "Elementary Numerical Analysis: An Algorithmic Approach", 3rd ed., McGraw-Hill, New York, 1980.

MAILING ADDRESS

Dr. E. Angelidis
Marathonos 22
Agia Paraskevi
GR-15343
Athens-GREECE