

Submitted to:

*IEEE Mediterranean Symposium on new Directions
in Control Theory and Application.*

Chania, Crete, Greece – June 21-23, 1993.

Experiments on Neural Control of a Flexible Manipulator

S. Panzieri

G. Ulivi

Dipartimento di Informatica e Sistemistica
Università degli Studi di Roma "La Sapienza"

Mailing address:

Dipartimento di Informatica e Sistemistica,
Via Eudossiana, 18 – 00184 ROMA, ITALY

Tel: (Italy)-6-44585869

Fax: (Italy)-6-44585367

E-Mail: panzieri@irmunisa.ing.uniroma1.it

ulivi@irmunisa.ing.uniroma1.it

Keywords: *Neural Networks, Flexible arms, Robot control, System identification.*

Abstract

Applications of neural networks (NN's) in the fields of identification, state estimation, and control of nonlinear dynamic plants have been recently developed [1] [2] [3]. Several neural models have been proposed to the aim of better replicate the dynamical behaviour of such systems [4] [5] [6]. Infact is well known that, given a sufficient number of training examples, NN's can learn a wide class of nonlinear mappings.

In this paper a multilayer neural network [7] is considered for the identification of a flexible robot arm. Measuring the position and the speed of a "sufficient" number of points along the link is feasible the reconstruction of the state space representation of the arm (rigid and elastic variables). Adequately exciting the system is then possible to obtain a training set including evolutions of sampled inputs and states. This set, opportunely scaled, is to be considered for feeding the NN. The resulting mapping is then used in a reverse way, to produce a suitable control to drive the robot along a trajectory, from an equilibrium point to an other, with fast modal damping characteristics.

Many problems arise when dealing with this particular mechanical system due to the presence of an unstable and unobservable dynamics: the transfer function between the torque applied at the joint level and the position of the end effector presents infact a non minimum phase structure [8]. Using the nonlinear regulator theory [10], it can be shown that exact tracking of a trajectory with internal stability admits only one evolution for the state variables. This leads to the impossibility of imposing a trajectory for the state without knowing the explicit form and the exact values of the parameters of the model.

After a short review of the model properties [9] it is shown in the paper how the series-parallel formulation for the identification model [1] is adequate. In this case its state Y_P is assumed depending from the previous states and from the input u of the real system:

$$Y_P(k+1) = \Phi[Y_P(k), Y_P(k-1), Y_P(k-2)] + u(k). \quad (1)$$

Given the above structure the NN can be trained to learn the nonlinear mapping between the delayed values of the plant states and the control input (see fig. 1). In this way th NN learns to emulate the inverse plant: when the desired state evolution is presented as its input, the NN computes a suitable plant control input. This approach




Figure 1: Training scheme




Figure 2: Control scheme

stress the nonlinear aspects of these control systems and their ability to work with a "black box" representation of the plant.

Using now the NN to control the link movement the scheme shown in fig 2 can be successfully adopted if the future desired state is fully known. In our case this model reference approach cannot be directly used because it is not possible to impose an evolution for the whole state without knowing the admissible one. So we can ask to the system only to have some properties, relaxing the condition of exact tracking.

The proposed control scheme has been implemented on the flexible arm available in the Robotics Laboratory at DIS [11] and experimental results are reported.

References

- [1] K.S. Narendra and K. Parthasarathy. Identification and control of dynamical system using neural networks. *IEEE Transaction on Neural Networks*, 1(1):4-27, 1990.

- [2] T. Yabuta and T. Yamada. Possibility of neural networks controller for robot manipulator. In *IEEE Conf. on Robotics and Automation*, pages 1686-1693, Cincinnati Ohio, May 1990.
- [3] S. Chen S. Billings and P. Grant. Nonlinear system identification using neural networks. *International Journal of Control*, 51(6):1191-1214, 1990.
- [4] M.M.Polycarpou and P.A.Ioannou Neural Networks as On-Line Approximators of Nonlinear Systems In *31th IEEE Conference on Decision and Control*, pages 7-12, Tucson, Arizona, Dec 1992.
- [5] Si-Zhao Quin Hong-Te Su and Thomas J. McAvoy. Comparison of four neural net learning methods for dynamic system identification. *IEEE Transaction on Neural Networks*, 3(1):122-130, 1992.
- [6] T. Fukuda T. Shibata M. Tokita and T. Mitsuoka. *Neural Servo Controller*. G.S. Buja, H. Fujita, and K. Ohnishi, 1990.
- [7] D. Psaltis A. Sideris and A. Yamamura. A multilayered neural network controller. *IEEE Control System Magazine*, pages 17-21, April, 1988.
- [8] De Luca A. and B. Siciliano Trajectory control of a non-linear one-link flexible arm *International Journal of Control*, 50(5):1699-1715, 1989.
- [9] De Luca A., Lanari L., Lucibello P., Panzieri S., and Ulivi G. Control experiments on a two-link robot with a flexible forearm. In *29th IEEE Conference on Decision and Control*, pages 520-527, Honolulu, HI, 1990.
- [10] De Luca A. Lanari L. and Ulivi G. Output regulation of a flexible robot arm. In *9th INRIA Int. Conf. on Analysis and Optimization of Systems*, pages 833-842, Antibes, France, 1990.
- [11] Lucibello P. Ulivi G. Design and realization of a two link direct drive robot with a very flexible forearm. Technical Report Rapp. DIS 16.89, Università di Roma "La Sapienza", Nov. 1989.