

NON INTEGER ORDER SYSTEMS

EMIL NIKOLOV

Technical University Sofia, Department Automation, Bulgaria, nicoloff@vmei.acad.bg

Abstract : The novelty in this working is the suggested class of astatic control systems. The article proposes: DASCROME and DASCROME_GSC structures; synthesis algorithm; robust analysis. The synthesis is based on the wave disturbances absorbing principle, non integer differentiation, gain scheduled control, parametric and structure independence of the stability margin.

Keywords: robust control, non integer order disturbance absorbing systems, robust analysis.

Introduction, Basic Relations. The robust features of the *CRONE* (Commande Robuste d'Ordre Non Entier) systems [13-15,17,19] are achieved by the parametric invariance of the stability margin. For example, for a linear parametric non-disturbed (nominal) system and for the corresponding parametric disturbed system in the multitude Π (1): G^* , G^I are the nominal and the disturbed at the highest level models of the plant G ; R^* - is the corresponding to G^* optimal controller; β^{nom} , β^{rep} - are models of the open-loop nominal disturbed in (1) systems; ω_u^{nom} , $\omega_u^{rep} = \omega_u^{nom} + \Delta\omega_u$ - are frequencies, corresponding to $|\beta^{nom}|=1$ and $|\beta^{rep}|=1$; $\Phi_m^{nom}(\omega_u^{nom})$, $\Phi_m^{rep}(\omega_u^{rep})$ - are the phase margins; ω_π^{nom} , $\omega_\pi^{rep} = \omega_\pi^{nom} + \nabla\omega_\pi$ - frequencies, corresponding to $\arg\beta^{nom} = -\pi$, $\arg\beta^{rep} = -\pi$; $B_m^{nom}(\omega_\pi^{nom})$, $B_m^{rep}(\omega_\pi^{rep})$ - are gain margins; $\Delta\omega_u$, $\nabla\omega_\pi$ - frequency variations, ℓ_a , ℓ_m - reparametrization ξ . The variations $\Delta\Phi_m$, ΔB_m of the disturbed in (1) system are (2), (3), as $\Delta\phi_p$ and $\Delta\phi_r$ - are the fluctuations in the plant and controller phases (4),(5).

$$\Pi = \left\{ \begin{array}{l} \ell_a = G^I(j\omega) - G^*(j\omega), |\ell_a| \leq \bar{\ell}_a(\omega) \\ \ell_m = \ell_a(j\omega)(G^*(j\omega))^{-1}, |\ell_m| \leq \bar{\ell}_m(\omega) \end{array} \right\} \quad (1)$$

$$\Delta\Phi_m = \Phi_m^{rep}(\omega_u^{rep}) - \Phi_m^{nom}(\omega_u^{nom}), (\Delta\phi_p + \Delta\phi_r) \quad (2)$$

$$\Delta B_m = B_m^{rep}(\omega_\pi^{rep}) - B_m^{nom}(\omega_\pi^{nom}), (|\beta_{\omega_\pi^{rep}}^{nom}| - |\beta_{\omega_\pi^{rep}}^{rep}|) \quad (3)$$

$$\Delta\phi_p(\Delta\omega_u, \ell_{a,(m)}) = \arg G(j\omega_u^{rep}) - \arg G^*(j\omega_u^{nom}) \quad (4)$$

$$\Delta\phi_r(\Delta\omega_u) = \arg R^*(j\omega_u^{rep}) - \arg R^*(j\omega_u^{nom}) \quad (5)$$

$$\left\{ \Delta\Phi_m = \Delta\phi_p + \Delta\phi_r, \left\{ \Delta\phi_p = -\Delta\phi_r \right\} \right\} \quad (6)$$

The solutions [13-15,17, 19] for the achievement of the parametric and structure invariance of Φ_m and/or of B_m to $|\ell_i(j\omega)| \leq \bar{\ell}_i(\omega)$ in (1) are in the synthesis of a controller R^{CRONE} , minimising (6). The criterion (7) of the synthesis is a definite shape (8) of β^{CRONE} (fig.1) in the range from 0 to $-\pi$ for all




fig.1

the frequencies $\omega_u^{rep} = f(\bar{\ell}_a, \bar{\ell}_m)$, named *gabarit vertical* $\beta^{gabarit\ vertical}$. When β^{CRONE} accepts the shape of $\beta^{gabarit\ vertical}$, (6) is satisfied, and ω_A, ω_B are the limit values of the frequency range of $\beta^{gabarit\ vertical}$ (fig.1). For the achievement of (7) and (8), R^{CRONE} is definite on the basis of (9), where: n - order of G^* (an whole number); n' , ($1 < n' < 2$) - non integer order of $R^{CRONE\ approx}$ (non whole number); m' , ($0 < m' < 1$; $m' > 1$) - non integer order of *CRONE* (non whole number). For the realisation of (9) in *CRONE* is used the non integer differentiation *DNE* (Dérivation Non Entière), realised by approximating *DNE_{approx}* derivator

$$R^{CRONE\ approx} \equiv R_N^{CRONE} \quad (10), (11),$$

$$\beta^{CRONE}(j\omega) \equiv \beta^{gabarit\ vertical}(j\omega), \forall \omega \in [\omega_A, \omega_B] \quad (7)$$

$$\beta_{(j\omega_u)}^{gabarit\ vertical} = \left(\frac{\omega_u}{j\omega} \right)^n, \arg \beta_{(j\omega_u)}^{gabarit\ vertical} \equiv \Phi_m^{nom} \equiv -n \cdot \frac{\pi}{2} \quad (8)$$

$$\arg R^{CRONE} = m' \cdot \frac{\pi}{2}, \forall \omega \in [\omega_A, \omega_B] \quad (9)$$

where: k_0 - is a static coefficient; ω_b - is the lower limit of $\Delta\omega_u$ in *DNE_{etalon}*; ω_h - is the upper limit of $\Delta\omega_u$ in *DNE_{etalon}*; N - an order of *DNE_{approx}* (whole number); ω_i, ω_i' - are the cut-off frequencies of the polynomial approximation *DNE_{approx}* with N zeros ω_i' and N poles ω_i . The approximation (10), (11)

is based on (12) in the range $(\omega_A \div \omega_B)$ and satisfied (9), where α, η are the recursive coefficients of DNE_{approx} . By the values of $N, \omega_i, \omega_i', \alpha, \eta$, the characteristic β^{CRONE} is constructed in a way, achieving *gabarit vertical*, and (6) as well. The robust analysis demonstrates the robust stability and performance of the *CRONE* - systems, their advantages in comparison with the classical systems, the presence of an error in the steady-state regime under control of static plants.

The models of the perturbations $\xi(t)$ [7-12,17,18] expressed by semi-determinate equations (13) are known. They are with given (chosen) $f_i(t)$ of the basis $\{f_i\}$ and with unknown parameters c_k , changing on

$$k_0 = \begin{cases} \left\{ a \frac{\left(I + \left(\frac{\omega_u}{\omega_h} \right)^2 \right)^{\frac{m'}{2}}}{I + \left(\frac{\omega_u}{\omega_b} \right)^2} \right\}, a = \frac{I}{|G^*(j\omega_u)|} \\ (0 < m' < I) \end{cases} \quad (10)$$

$$k_0 = \begin{cases} \left\{ a \frac{\left(I + \left(\frac{\omega_u}{\omega_h} \right)^2 \right)^{\frac{m'}{2}}}{I + \left(\frac{\omega_u}{\omega_b} \right)^2} \prod_{i=1}^N \left[\frac{I + \left(\frac{\omega_u}{\omega_i} \right)^2}{I + \left(\frac{\omega_u}{\omega_i'} \right)^2} \right]^{\frac{l_i}{2}} \right\} \\ (m' > I; m_e' + m_n' = m') \end{cases}$$

$$R_N^{CRONE} = \begin{cases} \left\{ k_0 \prod_{i=1}^N \frac{\left(I + \frac{j\omega}{\omega_i'} \right)}{\left(I + \frac{j\omega}{\omega_i} \right)} \right\} \\ (0 < m' < I) \end{cases} \quad (11)$$

$$R_N^{CRONE} = \begin{cases} \left\{ k_0 \frac{\left(I + \frac{j\omega}{\omega_b} \right)^{m_e'}}{I + \frac{j\omega}{\omega_h}} \prod_{i=1}^N \frac{\left(I + \frac{j\omega}{\omega_i'} \right)}{\left(I + \frac{j\omega}{\omega_i} \right)} \right\} \\ (m' > I; m_e' + m_n' = m') \end{cases}$$

$$\left\{ \begin{aligned} m' \frac{\pi}{2} (\log \alpha + \log \eta) &= \frac{\pi}{2} \log \alpha, \left(\frac{\omega_i}{\omega_i'} = \alpha; \frac{\omega_{i+1}}{\omega_i} = \eta \right) \\ R_m^{CRONE}(j\omega) &\equiv R_N^{CRONE}(j\omega), \forall \omega(\bar{\ell}_a, \bar{\ell}_m) \in [\omega_A, \omega_B] \end{aligned} \right\} \quad (12)$$

jumps their values under interval-permanent algorithm. The creation of (13) demands a choice of a suitable basis and the determination of its corresponding wave model of the state of This model is the differential equation, which solution is $\xi(t)$ (13). The determination of an unknown equation on its solution $\xi(t)$ is an inverse task. It is quite enough only one solution to be found. The convergence of the solving procedure is guaranteed by the next conditions execution.

$$\xi(t) = c_1 f_1(t) + c_2 f_2(t) + \dots + c_M f_M(t), (M = L) \quad (13)$$

$$f_i(p) = L[f_i(t)] = P_{k_i}(p) Q_{l_i}^{-1}(p), (0 \leq k_i \leq l_i \leq \infty) \quad (14)$$

The necessary condition is - each element of the basis to respond to (14). If c_i are treated as a constants - (15) is valid. The sufficient condition is Q of the rank ρ to be

$$\xi(p) = L[\xi(t)] = \sum_{i=1}^M c_i \frac{P_{k_i}(p)}{Q_{l_i}(p)} = \frac{P(p)}{Q(p)} \quad (15)$$

$$Q(p) = p^\rho + q_\rho p^{\rho-1} + \dots + q_2 p + q_1, (\rho \leq \sum_{i=1}^M l_i) \quad (16)$$

$$W(p) = Q^{-1}(p) \quad (17)$$

described by (16). Therefore, ξ is presented as 'an output variable' of a fictitious linear dynamical system W (17) under initial conditions $\{\xi(0), \dot{\xi}(0), \ddot{\xi}(0), \dots\}$, that determine P . Thus (13) satisfies the solution of (18), where q_i are apriori known, do not depend on c_i and are

$$\frac{d^\rho \xi(t)}{dt^\rho} + q_\rho \frac{d^{\rho-1} \xi(t)}{dt^{\rho-1}} + \dots + q_1 \xi(t) = 0 \quad (18)$$

$$\frac{d^\rho \xi(t)}{dt^\rho} + q_\rho \frac{d^{\rho-1} \xi(t)}{dt^{\rho-1}} + \dots + q_1 \xi(t) = \vartheta(t) \quad (19)$$

$$R^{DAS}(p) = \frac{P_c(p)}{Q_{c1}(p) Q_{c2}(p)} \quad (20)$$

determined by $\{f_i\}$. This is the solution of the inverse task. It gives an account of the changes of c_i under interval-permanent algorithm if in (18) is added external generating function $\vartheta(t)$. So, the wave model of the state of ξ is (19). Disturbance Absorbing System (*DAS*) use the model of the apriori uncertainty (19), given in the process of the *DAS*-design by suitable processing, approximation and wave modelling of a representative trend of a functioning industrial system. In *DAS* [7-12,17,18] is used the principle of the wave structured disturbances absorbing. For the scalar case it determines the controller $R^{DAS}(p)$ in *DAS* as (20). The polynomials P_{c1}, Q_{c1} are designed according to desired control plant function. Received from the industrial trend approximation, Q_{c2} (16) forms the feature of R^{DAS} to absorb ξ , defines the absorber (an integrator of a high non integer order *INE*) in *DAS* and corresponds to the characteristic polynomial (15).

Gain scheduled control systems *GSCS* [1-6,16,17], are designed for planned parametric changes in the controller, in conformity with the changes of measurable regime factors (under apriori known plant parameters dependence on the factors). For some *GSCS* the criterion for the synthesis is the stabilization of the system gain coefficient $k_{SYSTEM}(\xi, s) = const$, as the regime factor is the loading of the control valve $s = (\Delta P_{lin} \Delta P_{valve}^{-1} + I)^{-1}$. The methods of the parametric balance for *GSCS* synthesis are known as well.

The aim of the article is: The merger of the features of *CRONE* - systems, *DAS* and *GSCS* in a new astatic class of robust systems - *DASCRONE* (Disturbances Absorbables Systèmes de Com-

mande Robuste d'Ordre Non Entier) [17,20] and *DASCRONE·GSC* (Disturbances Absorbables Systèmes de Commande Robuste d'Ordre Non Entier type Gain Scheduled Contrôle), and proposing algorithms for their design.

Task's formulation. Given (21)-(29) or known are (Tabl.1): G^* , G^{II} , Π , the cut-off frequency

ω_c^{nom} of G^* , the local performance criterion Φ_m and the exploit change ranges of the set point - y^o , the loading - s and the reparametrization - $\bar{\ell}_a, \bar{\ell}_m$. It is necessary astatic non integer order control systems *DASCRONE* and *DASCRONE·GSC* to be designed.

Tabl.1

given / results		algorithm for synthesis	
(21)	$G^*(p)$	$1,239 e^{-2p} (10p+1)^{-1}$	(30) $N \geq 5$ (DNE)
(22)	$G^{II}(p)$	$4,96 e^{-14p} (10p+1)^{-1}$	(31) $\omega_u > 250 \omega_c^{nom}$ (DNE)
(23)	ω_c^{nom}	$0,08775 \text{ rad/sec}$	(32) $\omega_A = 0,1 \omega_u$ (DNE)
(24)	n	3	(33) $\omega_B = 10 \omega_u$ (DNE)
(25)	Φ_m	50°	(34) $\omega_b = 0,2 \omega_A$ (DNE)
(26)	$y^o(t)$	$10\% \leq y^o(t) \leq 90\%$	(35) $\omega_h = 1,2 \omega_B$ (DNE)
(27)	$s(t)$	$10\% \leq s(t) \leq 90\%$	(36) $n' = 2(1 - \pi^{-1} \Phi_m^{nom})$ (DNE)
(28)	$\bar{\ell}_a$	$4,96 e^{-14p} (10p+1)^{-1} - 1,239 e^{-2p} (10p+1)^{-1}$	(37) $m' = n - n'$ (DNE)
(29)	$\bar{\ell}_m$	$\frac{4,96 e^{-14p} (10p+1)^{-1}}{1,239 e^{-2p} (10p+1)^{-1}} - 1$	(38) $\alpha = (\omega_h \omega_b^{-1})^{(1,1+m')}$ (DNE)
(44)	$R^{PID}(p)$ CLASS	$0,13(5p+1)(5p)^{-1}(2p+1)(0,4p+1)^{-1}$	(39) $\eta = \left[(\omega_h \omega_b^{-1})^{\frac{1}{N}} \right]^{(-0,1-m')}$ (DNE)
(45)	R_N^{CRONE} DNE	$0,006 \left[\begin{aligned} &\left(\frac{1+0,0009p}{1+0,5696p} \right) \left(\frac{1+0,8666p}{1+0,1042p} \right) \times \\ &\times \left(\frac{1+0,2411p}{1+0,0289p} \right) \left(\frac{1+0,0670p}{1+0,0080p} \right) \times \\ &\times \left(\frac{1+0,0186p}{1+0,0022p} \right) \left(\frac{1+0,0052p}{1+0,0006p} \right) \end{aligned} \right]$	(40) $\left\{ \begin{aligned} \omega_{i+1}' &= (\alpha \eta)^i \cdot \eta^{\frac{1}{2}} \omega_b \\ \omega_{i+1} &= (\alpha \eta)^i \cdot \alpha \cdot \eta^{\frac{1}{2}} \omega_b \end{aligned} \right\}$ (DNE)
(46)	$R^{DAS}(p)$ INE	$\frac{0,0000845}{(p^2 + 2p^2 + p)}$	(41) $k_o = \begin{cases} k_{o1}, (0 < m' < 1) \\ k_{o2}, (m' > 1; m' + m_n' = m') \end{cases}$ (DNE)
(47)	$\nabla \ell$ GSC	$0,5(e^{2n(1-l)} - 1)(0,99 n s e^{2n(1-l)})^{-1} \nabla s$	(42) $\nabla \ell = -k_{s_0} k_{\ell}^{-1} \nabla s$ (GSC)
(48)	∇a GSC	$k_{SYSTEM}^{opt} (k_p^{opt})^{-1} \Delta l (\Delta y)^{-1}$	(43) $\nabla a = k_{SYSTEM}^{opt} (k_p^{opt})^{-1} \Delta l (\Delta y)^{-1}$ (GSC)




fig.2

Method for solving the task. Proposed are:

A. Structures of *DASCRONE* (fig.2) and *DASCRONE·GSC* (fig.3); **B.** Methods for: the parametric and structure invariance of the stability by a polynomial recursive approximation of *DNE*; the wave structured disturbances absorbing by *INE*; the parametric balance in *GSC* for *DASCRONE* and *DASCRONE·GSC* synthesis; **C.** Algorithm (30)-(41) for *DNE_{approx}*-component design (fig.4) under criterion *gabarit vertical U - contour*, guaranteeing (fig.5) the invariance of Φ_m and B_m




fig.3

to $\xi \in |\ell_i(j\omega)| \leq \bar{\ell}_i(\omega)$; **D.** Algorithm for *INE*-component design, based on the determination of the model of ξ (13), by analysis and a trend approximation $y_i(\varepsilon_i)$ in the system with *DNE_{approx}*-component under exploit conditions; **E.** Algorithm for *INE*-synthesis as a systematisation of character wave models (Tabl.2). Among them, by a visual analysis and comparison, is chosen suitable $\{f_i\}$ for modelling of ξ in the trend. In Tabl.2 are determined the corresponding models ξ^* (19), and the absorbers of the *INE*-

component; **F.** Algorithm [16,17] for *GSC*- component design, that determines the compensating variables as (42)(43), knowing the kind of the valve.




fig.4

Numerical example. A numeral example according to the data shown in Tabl.1 is solved (21)-(29) using the proposed methods and algorithms. The solution is illustrated by (44)-(48).




fig.5

Tabl.2

trend & $\xi(t) \Rightarrow$ model	$Q_{C2}^{DAS}(j\omega) INE$	trend & $\xi(t) \Rightarrow$ model	$Q_{C2}^{DAS}(j\omega) INE$
$\xi(t) = c_1 + c_2 t$ $\{f_i(t)\} = \{1, t\}$	$\frac{d^2 \xi}{dt^2} = v(t)$	$\xi(t) = (c_1 + c_2 t)e^{-\alpha t} + (c_3 + c_4 t)e^{-\beta t}$ $\{f_i(t)\} = \{e^{-\alpha t}, t e^{-\alpha t}, e^{-\beta t}, t e^{-\beta t}\}$	$\frac{d^2 \xi}{dt^2} + \alpha \frac{d \xi}{dt} = v(t)$
$\xi(t) = c_1 + c_2 t + c_3 t^2$ $\{f_i(t)\} = \{1, t, t^2\}$	$\frac{d^3 \xi}{dt^3} = v(t)$	$\xi(t) = c_1 + c_2(1 - e^{-\alpha t})$ $\{f_i(t)\} = \{1, (1 - e^{-\alpha t})\}$	$\frac{d^2 \xi}{dt^2} + \alpha \frac{d \xi}{dt} = v(t)$
$\xi(t) = c_1 + c_2 t + c_3 t^2 + c_4 t^3$ $\{f_i(t)\} = \{1, t, t^2, t^3\}$	$\frac{d^4 \xi}{dt^4} = v(t)$	$\xi(t) = c_1 + c_2(1 - e^{-\alpha t}) + c_3 t e^{-\alpha t}$ $\{f_i(t)\} = \{1, (1 - e^{-\alpha t}), t e^{-\alpha t}\}$	$\frac{d^3 \xi}{dt^3} + \alpha \frac{d^2 \xi}{dt^2} + \beta \frac{d \xi}{dt} = v(t)$
$\xi(t) = c_1 + c_2 e^{-\alpha t}$ $\{f_i(t)\} = \{1, e^{-\alpha t}\}$	$\frac{d^2 \xi}{dt^2} + \alpha \frac{d \xi}{dt} = v(t)$	$\xi(t) = c_1 + c_2(1 + (\alpha - 1)e^{-\alpha t}) + c_3((1 - \alpha)t + \alpha)e^{-\alpha t}$ $\{f_i(t)\} = \{1, 1 + (\alpha - 1)e^{-\alpha t}, ((1 - \alpha)t + \alpha)e^{-\alpha t}\}$	$\frac{d^3 \xi}{dt^3} + \alpha \frac{d^2 \xi}{dt^2} + \beta \frac{d \xi}{dt} = v(t)$
$\xi(t) = c_1 + c_2 e^{-\alpha t} + c_3 e^{-\beta t} + c_4 e^{-\gamma t}$ $\{f_i(t)\} = \{1, e^{-\alpha t}, e^{-\beta t}, e^{-\gamma t}\}$	$\frac{d^3 \xi}{dt^3} + (\alpha + \beta + \gamma) \frac{d^2 \xi}{dt^2} + (\alpha\beta + \alpha\gamma + \beta\gamma) \frac{d \xi}{dt} + \alpha\beta\gamma \xi = v(t)$	$\xi(t) = c_1 + c_2 t e^{-\alpha t} + c_3 t e^{-\beta t} + c_4 t e^{-\gamma t}$ $\{f_i(t)\} = \{1, 2, t e^{-\alpha t}, (t+2)e^{-\beta t}, e^{-\gamma t}\}$	$\frac{d^4 \xi}{dt^4} + (\alpha^2 + \beta^2 + \gamma^2) \frac{d^3 \xi}{dt^3} + (1 + 2\alpha) \frac{d^2 \xi}{dt^2} + \alpha \frac{d \xi}{dt} = v(t)$
$\xi(t) = c_1 + c_2 t + c_3 t^2 + c_4 t^3 + c_5 e^{-\alpha t} + c_6 e^{-\beta t} + c_7 e^{-\gamma t}$ $\{f_i(t)\} = \{1, t, t^2, t^3, e^{-\alpha t}, e^{-\beta t}, e^{-\gamma t}\}$	$\frac{d^5 \xi}{dt^5} + (\alpha + \beta + \gamma) \frac{d^4 \xi}{dt^4} + (\alpha\beta + \alpha\gamma + \beta\gamma) \frac{d^3 \xi}{dt^3} + \alpha\beta\gamma \frac{d^2 \xi}{dt^2} + \alpha\beta\gamma \xi = v(t)$	$\xi(t) = c_1 + c_2 \sin(\alpha t) + c_3 \cos(\alpha t) + c_4 \sin(\beta t) + c_5 \cos(\beta t)$ $\{f_i(t)\} = \{1, \sin(\alpha t), \cos(\alpha t), \sin(\beta t), \cos(\beta t)\}$	$\frac{d^2 \xi}{dt^2} + (\alpha^2 + \beta^2) \frac{d \xi}{dt} + \alpha^2 \beta^2 \xi = v(t)$




fig.6




fig.7






fig.9



Modelling. Robust analysis. The nominal *NOM* (fig.6), the classical *CLASS* (fig.7), *DASCONE* (fig.2) and *DASCONE · GSC* (fig.3) systems are modelled. The results of the simulations, functions of ω, ξ, s , and functions of t, y, ξ, s , demonstrate: the stability (fig.8, fig.9); the rejector features, the astathysm and the zero sensitivity (fig.10, fig.11); the robust stability and robust performance (fig.12) of *DASCONE* and *DASCONE · GSC* for the multitude Π (21)-(29).

Results based on the simulation analysis.

The simulation results (44)-(48), functions of ω, ξ, s , and functions of t, y, ξ, s , for the numerical example (21)-(29), confirm the reduced (fig.13) hydro-dynamical losses (49) [21] and






fig.11



the increased (fig.14) dynamical precision (50) [17] of *DASCONE* and *DASCONE · GSC* in comparison with *CLASS* in the principle and for the multitude Π (21), (22), (26)-(29) as well.

$$(49) [\Delta \hat{E}] = a s (1 - s (1 - e^{-2n(1-l)}))^{-0.5}, (a = \text{const})$$

$$(50) [\hat{e}(t)] = \left[1 - \left(\int_0^t \hat{e}^{\text{DASCONE}}_{\text{DASCONE} \cdot \text{GSC}}(t, y', s, \xi) dt \right) / \left(\int_0^t \hat{e}^{\text{CLASS}}(t, y', s, \xi) dt \right) \right]$$

Conclusions. The proposed in the article principally new astatic class systems *DASCONE* and *DASCONE · GSC*: merge effectively the features of *DAS*, *GSCS* and *CRONE* - systems; they are systems possessing proven robust features and confirmed high effectiveness under industrial conditions.

fig.12.a




fig.12.b





fig.13.a



variables du système, perturbations, disturbances fig.14.a




fig.14.b





fig.13.b



Bibliography

1. Banach A., W. Baumann (1990), Gain-scheduled control of partial differential equations. *Proceedings of the 29th Conference on Decision and Control*, 387-392
2. Shamma J., M. Athans (1987), Stability and robustness for slowly time-varying linear systems. *Proceedings of the 26th Conference on Decision and Control*, 434-439
3. Shamma J., M. Athans (1988), Guaranteed properties for nonlinear gain scheduled control systems. *Proceedings of the 27th Conference on Decision and Control*, 2202-2208
4. Shamma J., M. Athans (1990), Analysis of gain scheduled control for nonlinear plants. *IEEE Trans. Auto. Control*, vol. 35, No 8, 898-907
5. Shamma J., M. Athans (1991), Gain scheduling: Potential hazards and possible remedies. *Proceed. American Contr. Conf.*, 516-521
6. Smith H., E. Davison (1972), Design of industrial regulators - Integral feedback and feedforward control. *Proc. IEE*, vol 119, No 8, 1210-1216
7. Johnson C.D. (1968), *IEEE Trans. Auto. Cont.*, AC 13, 416
8. Johnson C.D. (1970), *IEEE Trans. Auto. Cont.*, AC 15, 222
9. Johnson C.D. (1970), *IEEE Trans. Auto. Cont.*, AC 15, 516
10. Johnson C.D. (1971), *IEEE Trans. Auto. Cont.*, AC 16, 635
11. Johnson C.D. (1972), *IEEE Trans. Auto. Cont.*, AC 17, 836
12. Johnson C.D. (1975), A Preliminary Study of Disturbance Absorbing Controllers, Redstone, Alabama
13. Oustaloup A. (1991), La commande CRONE (commande robuste d'ordre non entier), © Hermès (Traité des Nouvelles Technologies - Sirie Automatique), Paris, 495 p.
14. Oustaloup A. (1994), La robustesse (analyse et synthèse de commandes robustes), © Hermès (Traité des Nouvelles Technologies - Sirie Automatique), Paris, 530 p.
15. Oustaloup A. (1996), La dérivation non entière (théorie, synthèse et applications), © Hermès (Traité des Nouvelles Technologies - Sirie Automatique), Paris, 508 p.
16. Nikolov E. (2000), Gain Scheduled Control System with Smart Actuator, - Conference Proceedings at 8th IEEE Mediterranean Conference on Control & Automation (MED 2000), University of Patras, GRECE, July 17-19, 2000
17. Nikolov E. (1999), Control Systems with Robust Features, - D. Sc. Thesis, Technical University of Sofia, Sofia, 70 p.
18. Nikolov E. (1998), Disturbance Absorbing Robust Systems, - Proceedings of the National Conference AUTOMATICA AND INFORMATICS '98, pp. 14-21, (in Bul.)
19. Nikolov E. (1998), Non Integer Order Robust Systems, - Proceedings of the National Conference AUTOMATICA AND INFORMATICS '98, pp. 22-28, (in Bul.)
20. Nikolov E. (1998), Non Integer Order Disturbances Absorbing Systems, - Automatica and Informatics, 3/1998, pp. 17-22
21. Nikolov E. (1995) Hydrodynamic losses in Control Valves, - Proceedings of the National Conference AUTOMATICA AND INFORMATICS '95, pp. 319-322, (in Bul.)